




## PVC FILM T5500 TRANSPARENT

5,00m width without welds  
Light permeability 66%  
Fire classification B-s1,d0 wg  
PN-EN13501-1+A1:2010  
Thickness 0,18mm  $\pm$  10%  
Surface weight 186,3 g/m<sup>2</sup>

66% light permeability



**Instytut Techniki Budowlanej**

Building Research Institute

Research and development works | Accredited Group of Laboratories |  
Notified Body N° 1488 | EOTA Member | Certified management  
systems ISO 9001, ISO 27001

### REACTION TO FIRE CLASSIFICATION REPORT IN ACCORDANCE WITH PN-EN 13501-1+A1:2010

Sponsor:	Prepared by:	Product name:
Grupa DPS Sp. z o.o. ul. Krakowska 85A 40-391 Katowice	Building Research Institute Filtrowa 1 str. 00-611 Warszawa, Poland	Stretched ceiling DPS from transparencies PVC film, symbol T5500/T303BS1D0
Classification report No.:	Date of issue:	
02091.1.1/16/Z00NZP	21.11.2016	

Stretched ceiling DPS from transparencies soft PVC film, symbol T5500/T303BS1D0  
- thickness 0,18 mm  
- width 5 m  
- surface mass 186,3 g/m<sup>2</sup>  
- PVC film with containing plasticizers and stabilizers  
The stretched ceilings from transparencies soft PVC film, symbol T5500/T303BS1D0  
is produced by Grupa DPS Sp. z o.o., ul. Krakowska 85A, 40-931 Katowice, Poland